

Wellpointing Capabilities by Pump Type

RL-300

12" Rotary Lobe



Max GPM:	2,400
Max CFM:	240
Wellpoint:	1,200' LF
Wellpoint System:	w/ (300) 1.5" x 20' ft Total Length Wellpoints

RL-200

8" Rotary Lobe



Max GPM:	1,300
Max CFM:	180
Wellpoint:	800' LF
Wellpoint System:	w/ (200) 1.5" x 20' ft Total Length Wellpoints

HC-150 SAFE

6" High CFM Centrifugal



Max GPM:	1,800
Max CFM:	102
Sock Drain:	600' LF
Wellpoint System:	w/ (150) 1.5" x 20' ft Total Length Wellpoints

DD-8

8" Double Diaphragm



Max GPM:	700
11001 01110	, , ,
Max CFM:	80
Wellpoint:	400' LF
Wellpoint System:	w/ (100) 1.5" x 20' ft Total Length Wellpoints

DV-6

6" Vacuum Assisted Double Diaphragm



Max GPM:	550
Max CFM:	60
Sock Drain:	240' LF
Wellpoint System:	w/ (100) 1.5" x 20' ft Total Length Wellpoints

DD-6 SAFE

6" Double Diaphragm



Max GPM:	550
Max CFM:	60
Wellpoint:	240' LF
Wellpoint System:	w/ (60) 1.5" x 20' ft Total Length Wellpoints

PP-150

6" Piston Pump



Max GPM:	400
Max CFM:	60
Wellpoint:	200' LF
Wellpoint System:	w/ (50) 1.5" x 20' ft Total Length Wellpoints